

PROYECTORES HERCULES

HERCULES FLOODLIGHTS




Desde 100W Hasta 500W
From 100W Up To 500W



**M
O
D
E
L
O
S**


Hércules FQ104

Model	Hércules FQ104		Intensity of illumination Intensidad Luminica	
Wattage	100W			
IP Grade	IP65, IK09			
Input	AC100-240V (50/60Hz)			
Emitting Angle	25°/ 60°/90°		Distance	LUX
CCT	WW (3000K) /NW (4000K) /PW (6000K)		2M	2042
LM	WW:8000LM/NW:8500LM/PW:9000LM		5M	326.7
CRI	WW:Ra85/NW:Ra85/PW:Ra85		8M	127.6




Hércules FQ204

Model	Hércules FQ204		Intensity of illumination Intensidad Luminica	
Wattage	200W			
IP Grade	I IP65, IK09			
Input	AC100-240V (50/60Hz)			
Emitting Angle	25°/ 60°/90°		Distance	LUX
CCT	WW (3000K) /NW (4000K) /PW (6000K)		2M	4075
LM	WW:16000LM/NW:17000LM/PW:18000LM		5M	652.0
CRI	WW:Ra85/NW:Ra85/PW:Ra85		8M	254.7




Hércules FQ304

Model	Hércules FQ304		Intensity of illumination Intensidad Luminica	
Wattage	300W			
IP Grade	IP65, IK09			
Input	AC100-240V (50/60Hz)			
Emitting Angle	25°/ 60°/90°		Distance	LUX
CCT	WW (3000K) /NW (4000K) /PW (6000K)		2M	6261
LM	WW:24000LM/NW:25500LM/PW:27000LM		3M	2783
CRI	WW:Ra85/NW:Ra85/PW:Ra85		5M	1002



Hércules FQ504

Model	Hércules FQ504		Intensity of illumination Intensidad Luminica	
Wattage	500W			
IP Grade	IP65, IK09			
Input	AC100-240V (50/60Hz)			
Emitting Angle	25°/ 60°/90°		Distance	LUX
CCT	WW (3000K) /NW (4000K) /PW (6000K)		2M	9349
LM	WW:40000LM/NW:42500LM/PW:45000LM		5M	1496
CRI	WW:Ra85/NW:Ra85/PW:Ra85		8M	584.3



Sistema Avanzado de Disipación
-Advanced Dissipation System



Válvula de Respiración para la refrigeración y evitar la condensación
- Respiration Valve for cooling and Preventing Condensation

CONTACTENOS

www.imexter.com / ventas@imexter.com

809-563-7158 / 809-263-7643 C/FANTINO FALCO #47, APTO 902. TORRE NACO 2000, ENS. NACO, DISTRITO NACIONAL. R.D

